





AGS 1

ART.NO: 3615 | GRAFFITI REMOVER

AGS 1 is a powerful graffiti and paint remover. For use on exterior and interior surfaces. For use on hard, non-porous surfaces and painted surfaces. Readily biodegradable.

AGS 1 is used on hard surfaces such as: metal, painted metal surfaces (good quality paint), treated wood, clinker, glazed brick, glass. AGS 1 effectively dissolves spray paint graffiti and permanent markers. In some cases when the graffiti is new, AGS 1 may also be used on porous surfaces.

INSTRUCTIONS FOR USE

Hard surfaces

Apply **AGS 1** on to a dry, clean rag or an absorbent paper towel and wipe away the graffiti. Turn over the cloth so that only the clean part is used to the graffiti. Avoid wiping over dissolved graffiti. If there is a grease build up then wipe it off with clean rag. In order to stop the dissolution process, simply apply water on the surface already covered with the graffiti. It is always recommended to make a test on a small part of the surface.

Porous surfaces

Apply **AGS 1** with a low pressure sprayer. Let dwell for 5-10 minutes. Jet off with hot water and high pressure, (90°C, 150 bar/2175 PSI). Lance nozzle spread should be 15 - 25 degrees and water flow should be 15 to 20 litres/minute, (4-5 gal/minute). If pigment shadows remain, use **AGS 60** or **AGS 65**.

Dosage

Use as concentrate.

Consumption

0,2-0,5 litre/m².

Storage

Store frost-free in original closed container.

Shelf life

Approximately 24 months in unopened container.

Precautions

Use protective gloves, clothing and glasses.

Technical data

- Yellowish liquid.
- Packaging: 5 or 25 litre plastic jerricans.
- Density: 1,09 kg/ltr.
- Mild odour.
- Flash point 99°C
- Contains: 1-butylpyrrolidin-2-one,
 1-methoxypropanol.

Marking

Warning



Harmful if swallowed. Causes skin irritation. Causes serious eye irritation.

Not classified as dangerous goods according to **ADR**. For more information, see <u>MSDS</u>

Modified: 2023-06-13