

SAFETY DATA SHEET

AGS 5 SR HAWK

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

AGS 5 SR HAWK

Product no.

3627/1

Unique formula identifier (UFI)

05C0-40XC-C00M-MV91

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Graffiti remover

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Trion Tensid AB

Svederusgatan 1-3

SE-75450 Uppsala

Sweden

+46 18 15 61 90

www.trion.se

Contact person

William Stomilovic

E-mail

info@trion.se

Revision

11/05/2023

SDS Version

7.0

Date of previous version

30/09/2022 (6.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).


See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Acute Tox. 4; H302, Harmful if swallowed. Skin Irrit. 2; H315, Causes skin irritation.





Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.2. Label elements

Hazard pictogram(s)



Signal word

Warning

Hazard statement(s)

Harmful if swallowed. (H302)

Causes skin irritation. (H315)

Causes serious eye irritation. (H319)

Precautionary statement(s)

General

Prevention

Wash hands thoroughly after handling. (P264)

Wear eye protection/protective gloves/protective clothing. (P280)

▼ Response

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. (P301+P312)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)

Rinse mouth. (P330)

Storage

-

▼ Disposal

Dispose of contents/container in accordance with local regulation. (P501)

▼ Hazardous substances

1-butylpyrrolidin-2-one potassium hydroxide

▼Additional labelling

UFI: 05C0-40XC-C00M-MV91

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. ▼ Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
1-butylpyrrolidin-2-one	CAS No.: 3470-98-2 EC No.: 222-437-8	25-40%	Acute Tox. 4, H302 Skin Irrit. 2, H315	

AGS 5 SR HAWK Page 2 of 16



	UK-REACH: Index No.:		Eye Irrit. 2, H319	
2-(2-ethoxyethoxy)ethanol	CAS No.: 111-90-0 EC No.: 203-919-7 UK-REACH: Index No.:	15-25%		
2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether	CAS No.: 112-34-5 EC No.: 203-961-6 UK-REACH: Index No.: 603-096-00-8	15-25%	Eye Irrit. 2, H319	[1], [3]
1-methoxy-2-propanol monopropylene glycol methyl ether	CAS No.: 107-98-2 EC No.: 203-539-1 UK-REACH: Index No.: 603-064-00-3	5-10%	Flam. Liq. 3, H226 STOT SE 3, H336	[1]
potassium hydroxide	CAS No.: 1310-58-3 EC No.: 215-181-3 UK-REACH: Index No.: 019-002-00-8	<2%%	Acute Tox. 4, H302 Skin Corr. 1B, H314 (SCL: 2.00 %) Skin Corr. 1A, H314 Skin Irrit. 2, H315 (SCL: 0.50 %) Eye Irrit. 2, H319 (SCL: 0.50 %)	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

- [1] European occupational exposure limit.
- [3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

▼ Ingestion

In the case of ingestion, contact a doctor immediately. If the person is conscious, give them water. DO NOT try to induce vomiting unless this is recommended by a doctor. Hold head facing down to prevent vomit from returning to the mouth and throat. Prevent shock by keeping the injured person warm and calm. Initiate immediate resuscitation if breathing stops. If unconscious, roll the injured person into recovery position. Call an ambulance.

AGS 5 SR HAWK Page 3 of 16



Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO_x)

Carbon oxides (CO / CO2)

Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. ▼ Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Because of the danger of self-ignition, any waste from the product, spray mist and soiled rags etc. are to be kept in a

AGS 5 SR HAWK Page 4 of 16



fire-proof place in air-tight containers, alternatively the waste is to be burned.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

4 - 25 Celcius

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. ▼ Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. ▼ Control parameters

2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m³): 67,5

Short term exposure limit (15 minutes) (ppm): 15

Short term exposure limit (15 minutes) (mg/m³): 101,2

1-methoxy-2-propanol monopropylene glycol methyl ether

Long term exposure limit (8 hours) (ppm): 100

Long term exposure limit (8 hours) (mg/m³): 375

Short term exposure limit (15 minutes) (ppm): 150

Short term exposure limit (15 minutes) (mg/m³): 560

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

potassium hydroxide

Short term exposure limit (15 minutes) (mg/m³): 2

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

1-butylpyrrolidin-2-one

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	10 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	17,4 mg/m3
Long term – Systemic effects - Workers	Inhalation	70,5 mg/m3
Long term – Systemic effects - General population	Oral	2,5 mg/kg bw/day
Short term – Systemic effects - General population	Oral	2,5 mg/kg bw/day

2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether

AGS 5 SR HAWK Page 5 of 16



Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	20 mg/kg/day
Long term – Local effects - Workers	Inhalation	67,5 mg/kbm 10 ppn
Long term – Systemic effects - Workers	Inhalation	67,5 mg/kbm 10 ppn
Short term – Local effects - Workers	Inhalation	101,2 mg/kbm
2-(2-ethoxyethoxy)ethanol		
Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	25 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	83 mg/kg bw/day
Long term – Local effects - General population	Inhalation	18 mg/m3
Long term – Local effects - Workers	Inhalation	30 mg/m3
Long term – Systemic effects - General population	Inhalation	37 mg/m3
Long term – Systemic effects - Workers	Inhalation	61 mg/m3
Long term – Systemic effects - General population	Oral	50 mg/kg bw/day
PNEC 1-butylpyrrolidin-2-one		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	0,8 mg/L
Freshwater sediment	Single	6,336 mg/kg
Marine water	Single	0,08 mg/L
Marine water sediment	Single	06336 mg/kg
Sewage treatment plant	Continuous	30,62 mg/L
Soil	Single	0,7955 mg/kg
Water	Single	1 mg/L
2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	1 mg/L
Freshwater sediment	Single	4,4 mg/kg
Marine water	Single	0,1 mg/L
Marine water sediment	Single	0,44 mg/kg
Sewage treatment plant	Single	200 mg/L
Soil	Single	0,32 mg/kg
2-(2-ethoxyethoxy)ethanol		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	1,98 mg/L
Freshwater sediment	Single	0,732 mg/kg
	<u> </u>	. 5 5

AGS 5 SR HAWK Page 6 of 16



Marine water sediment	Single	7,32 mg/kg
Sewage treatment plant	Single	500 mg/L
Soil	Single	0,34 mg/kg

8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

▼ Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Туре	Class	Colour	Standards
Respiratory protection	-	-	-
is not needed in the			
event of adequate			
ventilation			

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	R

Hand protection

iana protection	and procession				
Material	Glove thickness (mm)	Breakthrough time (min.)	Standards		
Latex	0.12	-	EN374-2		

Eye protection

Туре	Standards	
Wear safety glasses with side shields.	EN166	

AGS 5 SR HAWK Page 7 of 16



SECTION 9: Physical and chemical properties

```
9.1. Information on basic physical and chemical properties
  Physical state
      Liquid
  Colour
     Tan
  Odour / Odour threshold
      Solvent
  На
      Testing not relevant or not possible due to nature of the product.
  Density (q/cm<sup>3</sup>)
      1.01
  Kinematic viscosity
      poise cm<sup>3</sup>/g
  Particle characteristics
      Does not apply to liquids.
Phase changes
  Melting point/Freezing point (°C)
      Testing not relevant or not possible due to the nature of the product.
  Softening point/range (waxes and pastes) (°C)
      Does not apply to liquids.
  Boiling point (°C)
      120-180
  Vapour pressure
      Testing not relevant or not possible due to the nature of the product.
  Relative vapour density
      Testing not relevant or not possible due to the nature of the product.
  Decomposition temperature (°C)
      Testing not relevant or not possible due to the nature of the product.
Data on fire and explosion hazards
  Flash point (°C)
      67
   ▼ Flammability (°C)
      230
   ▼ Auto-ignition temperature (°C)
      Testing not relevant or not possible due to the nature of the product.
  Lower and upper explosion limit (% v/v)
      1.1 - 10.6
Solubility
  Solubility in water
      Completely soluble
  n-octanol/water coefficient
      Testing not relevant or not possible due to the nature of the product.
  Solubility in fat (q/L)
      Testing not relevant or not possible due to the nature of the product.
```

9.2. Other information

AGS 5 SR HAWK Page 8 of 16



Other physical and chemical parameters

No data available.

▼ Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

▼ Acute toxicity

Product/substance 1-butylpyrrolidin-2-one

Species: Rat
Route of exposure: Oral
Test: LD50

Result: 300-2000 mg/kg ·

Product/substance 1-butylpyrrolidin-2-one

Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: >2000 mg/kg ·

Product/substance 2-(2-ethoxyethoxy)ethanol

Species: Rat
Route of exposure: Oral
Test: LD50

Result: 6031 mg/kg bw ·

Product/substance 2-(2-ethoxyethoxy)ethanol

Species: Rabbit
Route of exposure: Dermal
Test: LD50

Result: 9143 mg/kg bw ·

Product/substance 2-(2-ethoxyethoxy)ethanol

Species: Rat

AGS 5 SR HAWK Page 9 of 16



Route of exposure: Inhalation Test: LD lo

Result: $0,025 \text{ mg/L} \cdot$

Product/substance 2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether

Species: Rat
Route of exposure: Inhalation
Test: LC50

Result: >29 ppm (2h) ·

Product/substance 2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether

Species: Rat
Route of exposure: Oral
Test: LD50
Result: 2410 mg/kg ·

Product/substance 2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether

Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: 2764 mg/kg ·

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Species: Rat
Route of exposure: Oral
Test: LD50
Result: 7200 mg/kg

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Species: Rabbit
Route of exposure: Dermal
Test: LD50
Result: 13000 mg/kg ·

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Species: Rat
Route of exposure: Inhalation
Test: LC 50 (6 Hours)
Result: 7200 ppm

Product/substance potassium hydroxide

Species: Rat
Route of exposure: Oral
Test: LD50
Result: 273 mg/kg ·

Harmful if swallowed.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

AGS 5 SR HAWK Page 10 of 16



Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ Endocrine disrupting properties

Not applicable.

▼ Other information

None known.

SECTION 12: Ecological information

12.1. ▼Toxicity

Product/substance 1-butylpyrrolidin-2-one

Species: Fish

Duration: 96 hours

Test: LC50

Result: >100 mg/L ⋅

Product/substance 1-butylpyrrolidin-2-one

Species: Algae
Duration: 72 hours
Test: EC50
Result: 130 mg/L⋅

Product/substance 1-butylpyrrolidin-2-one

Species: Daphnia
Duration: 48 hours
Test: EC50
Result: >100 mg/L ·

Product/substance 2-(2-ethoxyethoxy)ethanol

Species: Fish

Duration: 96 hours

Test: LC50

Result: $6010 \text{ mg/L} \cdot$

AGS 5 SR HAWK Page 11 of 16



Product/substance 2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether

Species: Fish

Duration: 96 hours

Test: LC50

Result: 1300 mg/l·

Product/substance 2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether

Species: Daphnia
Duration: 72 hours
Test: EC50
Result: >100 mg/l·

Product/substance 2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether

Species: Algae
Duration: 96 hours
Test: EC50
Result: >100 mg/l·

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Species: Fish
Duration: 96 hours
Test: LC50
Result: 20800 mg/L

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Species: Daphnia
Duration: 96 hours
Test: EC50
Result: 23300 mg/L

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Species: Algae
Duration: 72 hours
Test: IC50
Result: >1000 mg/L

Product/substance potassium hydroxide

Species: Fish

Duration: 24 hours

Test: LC50

Result: 80 mg/L ·

12.2. ▼Persistence and degradability

Product/substance 1-butylpyrrolidin-2-one

Biodegradable: Ye Test method:

Result:

Product/substance 2-(2-ethoxyethoxy)ethanol

Biodegradable: Yes

Test method: Oxygen consumption

Result: 79,4%

AGS 5 SR HAWK Page 12 of 16



Product/substance 2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether

Biodegradable: Yes

Test method: OECD 301 B Result: 100%

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Biodegradable: Yes
Test method: OECD 301 E
Result: 96%

Product/substance potassium hydroxide

Biodegradable: Ye

Test method: Result:

12.3. ▼ Bioaccumulative potential

Product/substance 1-butylpyrrolidin-2-one

Test method:

Potential bioaccumulation: No

LogPow: No data available. BCF: No data available.

Other information:

Product/substance 2-(2-ethoxyethoxy)ethanol

Test method:

Potential bioaccumulation: No

LogPow: No data available. BCF: No data available.

Other information:

Product/substance 2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether

Test method:

Potential bioaccumulation: No LogPow: 1,0000

BCF: No data available.

Other information:

Product/substance 1-methoxy-2-propanol monopropylene glycol methyl ether

Test method:

Potential bioaccumulation: No LogPow: <3

BCF: No data available.

Other information:

Product/substance potassium hydroxide

Test method:

Potential bioaccumulation: No LogPow: -1,3800

BCF: No data available.

Other information:

12.4. ▼ Mobility in soil

1-methoxy-2-propanol monopropylene glycol methyl ether

AGS 5 SR HAWK Page 13 of 16



LogKoc = 1.699, High mobility potential.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. ▼Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

13.1. ▼ Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 4 - Irritant (skin irritation and eye damage)

HP 6 - Acute toxicity

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

After dilution with water, small quantities are permitted to go to water treatment plants. Empty packages and product residues must be handled in an environmentally correct manner according to applicable laws and provisions. The company is affiliated to REPA. Do not attempt to refill or clean the package.

EWC code

20 01 29*

Detergents containing dangerous substances

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 14.2 UN / ID UN proper shipping name	14.3 Hazard class(es)	14.4 14.5 PG* Env**	Other information:
ADR		-		-
IMDG		-		-
IATA		-		-

^{*} Packing group

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Restrictions for application

Restricted to professional users.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

AGS 5 SR HAWK Page 14 of 16

^{**} Environmental hazards



Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Not applicable.

▼ REACH, Annex XVII

2-(2-butoxyethoxy)ethanol diethylene glycol monobutyl ether is subject to restrictions, UK-REACH annex XVII (entry 55).

Additional information

Not applicable.

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

H226, Flammable liquid and vapour.

H302, Harmful if swallowed.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

AGS 5 SR HAWK Page 15 of 16



LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

▼ The safety data sheet is validated by

RO

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en