



# AGS 5 SR HAWK

ART. NO: 36271 | GRAFFITI REMOVER

**AGS 5 SR HAWK** is a specially developed graffiti remover for removal of shadowing from most types of permanent markers or felt-tip pen graffiti and leather dyes. For use on exterior and interior surfaces. **AGS 5 SR HAWK** may be used on most surfaces.

**AGS 5 SR HAWK** effectively removes graffiti and shadowing from most types of permanent marker or felt-tip pens. Can also be used on spray-paint.

**AGS 5 SR HAWK** may be used on most surfaces. Hard non-porous surfaces, such as painted substrates.

**AGS 5 SR HAWK** has shown to be very effective to solve difficult leather dye pigments.

## INSTRUCTIONS FOR USE

Apply **AGS 5 SR HAWK** on to a dry, clean cloth or an absorbent paper towel and wipe away the graffiti. Turn over the cloth so that only the clean part is used to remove the graffiti. Avoid wiping over dissolved graffiti. If there is a grease build up then wipe it off with clean cloth. In order to stop the dissolution process, simply apply water on the surface already covered with the graffiti. If shadows remain use [AGS 60](#) or [AGS 65](#).

**NB!** It is always recommended to make a test on a small part of the surface.

## Dosage

Use as concentrate.

## Consumption

0,1 - 0,3 litre/m<sup>2</sup>.

## Storage

Store frost-free in closed original container.

## Shelf life

Approximately 24 months in unopened container.

## Technical data

- Brownish liquid.
- Packaging: 5, and 25 litre plastic jerricans.
- Density: 0,97 kg/litre.
- Flash point: 67°C
- Faint scent of lime and solvents.
- Contains: 1-butylpyrrolidin-2-one, 1-methoxypropanol, potassium hydroxide.

## Precautions

Use protective gloves, clothing and glasses.

## Marking

Warning



Harmful if swallowed. Causes skin irritation. Causes serious eye irritation.

Not classified as dangerous goods according to **ADR**. For more information, see [MSDS](#).

Modified: 2023-06-13

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and are responsible for the result.