



Svederusgatan 1-3, SE-754 50 Uppsala, Sweden. Tel: +46 18-15 61 90.

email: info@trion.se. www.trion.se



# AGS 5 SR

ART. NO: 3627 | GRAFFITI REMOVER

**AGS 5 SR** is a specially developed graffiti remover for removal of shadowing from most types of permanent markers or felt-tip pen graffiti and leather dyes. For use on exterior and interior surfaces. **AGS 5 SR** may be used on most surfaces.

**AGS 5 SR** effectively removes graffiti and shadowing from most types of permanent marker or felt-tip pens. Can also be used on spray-paint.

**AGS 5 SR** may be used on most surfaces. Hard non-porous surfaces, such as painted substrates. Porous surfaces, such as concrete, brick, sandstone, limestone, etc. **AGS 5 SR** has shown to be very effective to solve difficult leather dye pigments.

## INSTRUCTIONS FOR USE

Apply **AGS 5 SR** on to a dry, clean rag or an absorbent paper towel and wipe away the graffiti. Turn over the cloth so that only the clean part is used to the graffiti. Avoid wiping over dissolved graffiti. If there is a grease build up then wipe it off with clean rag. In order to stop the dissolution process, simply apply water on the surface already covered with the graffiti. If shadows remain use **AGS 60** or **AGS 65**.

**NB!** It is always recommended to make a test on a small part of the surface.

# Dosage

Use as concentrate.

#### Consumption

0,1-0,3 litre/m².

## Storage

Store frost-free in closed original container.

#### Shelf life

Approximately 24 months in unopened container.

#### **Precautions**

Use protective gloves clothing and glasses.

## Technical data

- Brownish liquid.
- Packaging: 5 litre plastic jerricans.
- Density: 0,97 kg/litre.
- Solvent odour.
- Flash point: 67°C
- Contains 1-butylpyrrolidin-2-one, hexyl D-glucoside, potassium hydroxide, 1-methoxypropanol.

### Marking

Warning



Harmful if swallowed. Causes skin irritation. Causes serious eye irritation.

Not classified as dangerous goods according to **ADR**. For more information, see <u>MSDS</u>.