



Svederusgatan 1-3, SE-754 50 Uppsala, Sweden. Tel: +46 18-15 61 90.

email: info@trion.se. www.trion.se



AGS 560

ART. NO: 3653 | GRAFFITI REMOVER

AGS 560 is a mild graffiti remover. For outside and indoor use. Preferable for hard non-porous surfaces: especially plexiglas and other painted surfaces. Biodegradable.

Material

AGS 560 is especially developed for removal of graffiti on plexiglass. Effectively removes marker felt-tip pen, leather dye and rust protective coating without attacking the plexiglass. AGS 560 is also effective on other painted and delicate surfaces. AGS 560 even works on spray paint graffiti, but the dissolving time is a little bit longer. Testing on a small surface prior to removal is recommended.

INSTRUCTIONS FOR USE

Graffiti removal

Use **AGS 560** on a clean cloth or absorbent paper and wipe off graffiti. Turn the cloth so that a clean part is always used. Avoid smears of dissolved graffiti and wipe off residues of **AGS 560**. Rinse with water and dry with a clean cloth.

The dissolving process is easily interrupted with water.

Dosage

Use as concentrate.

Consumption

0,2 - 0,5 litre/m².

Storage

Store frost-free in closed original container.

Shelf life

Approximately 24 months in unopened container.

Precautions

Use protective gloves and glasses.

Technical data

- Brownish liquid.
- Packaging: 1 litre plastic bottle or 5 litre plastic jerricans.
- Density: 0,92 kg/litre.
- Mild odour.
- Flash point: >108°C
- Contains 2-(2-Ethoxyethoxy) ethanol, n-butylpyrrolidone

Marking

Not classified

Not classified as dangerous goods according to **ADR**. For more information, see **MSDS**.