



AGS 65

ART. NO: 3665 | SHADOW REMOVER

AGS 65 is used for removal of graffiti-shadows in conjunction with graffiti removal. Slightly thickened for increased dwelling time. Readily biodegradable. For use on exterior and interior surfaces. Primarily used on porous surfaces.

AGS 65 removes shadowing left on surfaces following graffiti removal, in special cases also paint removal.

AGS 65 is formulated for use on the following materials: granite, slate, sand-stone, glazed brick, treated marble, wood and non-organic paint. **AGS 65** is slightly thickened to cling on surface and increase the dwelling time.

NB! Do not use **AGS 65** on soft metal surfaces such as aluminium.

INSTRUCTIONS FOR USE

Graffiti-shadow removal

Apply **AGS 65** with a brush on wet surface, leave to dwell for 5 - 30 minutes until graffiti/shadowing has dissolved. Jet off with high-pressure hot water, (40-90°C, 70-150 bar/1015-2175 PSI). Adjust pressure to suit surface condition.

NB! For metal surfaces, the effectiveness can be reduced if the pressure is too high. A better result can be achieved if the surface is wiped with a sponge or cloth in the rinsing process. Repeat the procedure if required.

Dosage

Use as concentrate.

Consumption

0,2 - 0,5 litre/m² per application using concentrate.

Storage

Store frost-free in closed original container.

Shelf life

Approximately 24 months in unopened container.

Precautions

Special caution must be taken, as **AGS 65** is a **CORROSIVE** product. Use protective gloves, clothing, and glasses. If product comes in contact with eyes, rinse with lot of water and immediately go to hospital. If in contact with the skin, rinse with lots of water, go to hospital if necessary.

Technical data

- Brownish slightly viscous fluid.
- Packaging: 5 or 25 litre plastic jerricans.
- Density: 1,09 kg/litre.
- pH-value approx. 14.
- Flash point: >67°C
- Contains Potassium hydroxide, hexyl D-glucoside, 2-Aminoethanol, 1-methoxypropanol.

Marking

Danger



Causes severe skin burns and eye damage.

Classified as dangerous goods according to ADR.

UN 1814, POTASSIUM HYDROXIDE SOLUTION

Class: 8 PG: II

For more information, see [MSDS](#).

Modified: 2023-06-13

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and are responsible for the result.