



AGS POWER BLUE GEL

ART. NO: 3801 | GRAFFITI REMOVER

AGS POWER BLUE GEL is a very powerful graffiti and shadow remover to be used in cold weather and on difficult graffiti. For use on porous exterior surfaces.

AGS POWER BLUE GEL is a slightly thickened graffiti remover to be used on porous surfaces such as: granite, brick, concrete, lime, tiles, etc. **AGS POWER BLUE GEL** dissolves spray-paint graffiti, permanent markers and leather dye graffiti.

NB! Do not use **AGS POWER BLUE GEL** on metal surfaces as aluminium. Make a test before graffiti removal.

INSTRUCTIONS FOR USE

Apply **AGS POWER BLUE GEL** with a brush. Agitate the surface well. Leave until graffiti has dissolved, 10-30 minutes depending on the surface, graffiti and weather conditions. Jet off with hot water and high pressure, 90°C, 150 bar/2175 PSI or adjust to the surface. Lance nozzle spread should be 15 - 25 degrees and water flow should be 15 to 20 litres/minute, (4-5 gal/minute).

In case of shadows, apply **AGS POWER BLUE GEL** as a shadow remover, wait for 5-10 minutes before jet off with high pressure. Make a final rinse with low pressure.

Dosage

Use as concentrate.

Consumption

0,5 - 1,0 litre/m².

Storage

Store frost-free in original closed container.

Shelf life

Approximately 24 months in unopened container.

Precautions

AGS POWER BLUE GEL is **CORROSIVE**, wear suitable protective gloves, clothing and glasses. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Technical data

- Light viscous dark brown fluid.
- Packaging: 5 or 25 litre plastic jerricans.
- Density: 0.99 kg/litre.
- Solvent odour.
- Flash point 46°C.
- pH value 14.
- Contains 1-butylpyrrolidin-2-one, potassium hydroxide, hydrogen treated naphtha

Marking

Danger



Flammable liquid and vapour. Harmful if swallowed. Causes severe skin burns and eye damage. Harmful to aquatic life with long lasting effects.

Classified as dangerous goods according to ADR

UN 1814, POTASSIUM HYDROXIDE SOLUTION.

Class: 8 PG: II

For more information, see [MSDS](#).

Modified: 2023-04-08

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and are responsible for the result.