



# BPS 7621 GEL

ART. NO: 7621 | PAINT REMOVER

**BPS 7621 GEL** is a biodegradable paint remover for surfaces painted with latex and dispersion paints. Removes both the top coat and primer in one go. Clings to vertical surfaces. User friendly.

## Instructions for use

Cover surfaces that do not need treatment, cover sensitive vegetation, and fence off the area. Apply **BPS 7621** with a brush, roller or spray gun. The gaskets in a spray gun have to with stand solvents. Allow to dwell on the surface until the paint has lifted. The dwell time can vary between 1-12 hours and depends on temperature, age of the paint, paint thickness, and surface conditions. In warm weather the dwell time can be shorter. The dissolved paint is jetted off with high pressure and hot water. (Pressure depending on surface, 50-300 bar/ 20 litre/ min., 25-45° angle nozzle, 90°C gives the best effect). Work from the bottom to the top. Always work from cleaned surface towards the paint. When the surface is cleaned, rinse off with low pressure from top to bottom.

**NB!** Always test on a smaller surface first.

## Dosage

Use as concentrate.

## Consumption

The consumption depends on thickness of paint and temperature. Normal usage is approximately 0,2 - 1,0 litre/ m<sup>2</sup>.

## Storage

Store frost-free in original container.

## Shelf life

24 months in unopened container.

## Precautions

Use protective gloves, clothes and glasses.

## Technical data

- Viscous white liquid with a weak odour.
- Packaging: 10 or 25 litre plastic jerricans.
- Density: 1,04 kg/litre.
- Flash point 100 °C.
- Contains benzyl alcohol.

## Marking

Warning



Harmful if swallowed or if inhaled.

Not classified as dangerous goods according to **ADR**.  
For more information, see [MSDS](#).

Modified: 2021-12-14

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and are responsible for the result.