



BETO

ART NO: 1302 | RUST REMOVER

BETO is a biodegradable product that dissolves and loosens rust on iron and steel surfaces. Used as a pickling agent on metal surfaces prior to painting. **BETO** is used in baths to restore old rusty tools to a usable condition.

BETO is effective to dissolve and loosen rust on iron and steel surfaces. **BETO** is also excellent as a pickling agent prior to painting galvanized surfaces (surfaces with zinc coating) and also prior to paint jobs on concrete floors.

BETO is used in baths to restore old rusty tools to a usable condition. **BETO** can in some cases replace blasting. **BETO** may after neutralization be released into the sewer.

BETO is mainly used in these areas:

- Industries
- Work shops
- Paint shops
- Building contractors
- Floor contractors
- Farms
- Estate management

Dosage

Use as concentrate or dilute with 1-8 parts of water.

Pickling of concrete floor: Dilute with 4 parts of water.

Consumption

Approx. 0,5-1 liter mixed product/m².

Storage

Store frost-free in original container.

Shelf life

Approximately 24 months in unopened container.

Precautions

BETO is CORROSIVE, use protective gloves, clothes and eye/face protection.

Technical data

- Transparent liquid.
- Packaging: 5 or 25 litre plastic jerricans.
- Density: 1,26 kg/litre.
- Low odour.
- pH approx. 1
- Contains phosphoric acid.

Marking

Danger



Causes severe skin burns and eye damage.

Classified as dangerous goods according to ADR.

UN 1805, PHOSPHORIC ACID SOLUTION

Class: 8 PG: III

For more information, see [MSDS](#).

Modified: 2023-03-09

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and are responsible for the result.