



# VEHICLE WASH

ART NO: 1110 | CLEANER AND DEGREASER

**VEHICLE WASH** is a combined cleaner and de-greaser. **VEHICLE WASH** is bio-degradable. Vehicle wash is used to clean all types of vehicles, engines, machine tools etc. Dissolves grease and road-salts.

**VEHICLE WASH** dissolves oil and grease dirt and road-salt. It belongs to the latest generation of "easily" biodegradable and user friendly cleaners. **VEHICLE WASH** cannot be used to clean plexiglas or to clean prior to paint-jobs.

**VEHICLE WASH** is primarily used for removal of:  
Ingrained chemically mixed asphalt, tar splashes, oil and grease, insects.

**VEHICLE WASH** is also used for:  
Engine wash, de-greaser, summer vehicle cleaner, rinsing with shiny effect

## Instructions for use

Rinse the surface to clean with water, apply Vehicle Wash with a low pressure spray. Allow to dwell for 5-15 minutes. Rinse off with hot water. Best results are achieved at water temperatures between 50-70°C in combination with brush wash.

## Dosage

- Ingrained chemically mixed asphalt and tar, dilute 1:1 with water
- Fresh tar, asphalt, road salt dilute 1:1 – 1:2 with water.
- Engine wash, degreaser, insects etc. dilute 1:2 – 1:4 with water
- Summer vehicle cleaner, dry dirt etc. dilute 1:30 with water.
- Rinse with shiny effect, dilute 1:200 with water.

## Storage

Store frost-free in original closed container. At temperatures above +30°C there is a risk that the product turns whiteish, cool down and shake well.

## Shelf life

Approximately 24 months in unopened container.

## Precautions

Use protective gloves and glasses.

## Technical data

- Clear liquid.
- Packaging: 5 or 25 litre jerricans.
- Density: 1,00 kg/litre.
- Odour free.
- pH-value 9,5.
- Contains Fatty alcohol ethoxylated.

## Marking

Danger



Causes serious eye damage.

Not classified as dangerous goods according to **ADR**.  
For more information, see [MSDS](#).

Modified: 2021-12-29

This product information is intended as a guide for use of this product. TRION TENSID AB cannot give any guarantee for end result achieved. Applicator of product shall carry out testing and are responsible for the result.