

Svederusgatan 1-3, SE-754 50 Uppsala, Sweden. Tel: +46 18-15 61 90.

email: info@trion.se. www.trion.se



AGS 25

ART. NO: 3657 | REMOVER FOR RUST PROTECTIVE SEALERS

AGS 25 is used for removal of graffiti, made from petroleum based rust protective sealers, or bitumen. **AGS 25** is used for removal of graffiti tags and murals on both smooth and porous surfaces. For use on exterior and interior surfaces. On porous surfaces: Use **AGS 25** in combination with **AGS 27 GEL.** Readily biodegradable.

AGS 25 is a readily biodegradable product used for removal of rust protective sealers, and bitumen.

AGS 25 may be used on most surfaces: hard non porous surfaces, such as polished stone surfaces, plastic, metal, or porous surfaces such as concrete, brick, granite, plaster etc.

INSTRUCTIONS FOR USE

Hard non porous surfaces:

When graffiti is spread over an extensive area, use a cloth with **AGS 25**. Neutralise with water.

Porous surfaces:

Apply **AGS 25** with low-pressure spray or brush, then apply **AGS 27 GEL** with a brush. Let dwell for 30 minutes - 5 hours, depending on weather conditions. Jet off with high-pressure hot water (70-90°C, approx. 150 bar, nozzle angle 15-25°, 20 litres/ min.). If required repeat the process.

NB! When cold weather, all graffiti removers need more time to dissolve the graffiti. Likewise, more time is required for thick layers and when substrate is porous.

Dosage

Use as concentrate.

Consumption

0,5-1,0 litre/m².

Storage

Store frost-free in closed original container.

Shelf life

Approximately 24 months in unopened container.

Precautions

Use protective gloves and glasses.

Technical data

- Clear liquid.
- Packaging: 5 litre plastic jerricans.
- Density: 1,0 kg/litre.
- Faint odour.
- Contains Fatty alcohol ethoxylated.

Marking

Danger



Causes serious eye damage.

Not classified as dangerous goods according to **ADR**. For more information, see <u>MSDS</u>.